


# **Belt Sander**

76 mm (3") MODEL 9924DB



003362



# INSTRUCTION MANUAL

# **⚠ WARNING:**

For your personal safety, READ and UNDERSTAND before using. SAVE THESE INSTRUCTIONS FOR FUTURE REFERENCE.

www.makitatools.com

# **SPECIFICATIONS**

Model	9924DB
Belt size	76 mm x 610 mm (3" x 24")
Belt speed	400 m/min. (1,300 ft./min.)
Overall length	355 mm (14")
Net weight	4.8 kg (10.6 lbs)

- Manufacturer reserves the right to change specifications without notice.
- · Specifications may differ from country to country.

# **GENERAL SAFETY RULES**

USA002-2

(For All Tools)

# **↑ WARNING:**

**Read and understand all instructions.** Failure to follow all instructions listed below, may result in electric shock, fire and/or serious personal injury.

# SAVE THESE INSTRUCTIONS

### Work Area

- Keep your work area clean and well lit.
   Cluttered benches and dark areas invite accidents.
- Do not operate power tools in explosive atmospheres, such as in the presence of flammable liquids, gases, or dust. Power tools create sparks which may ignite the dust or fumes.
- Keep bystanders, children, and visitors away while operating a power tool. Distractions can cause you to lose control.

# **Electrical Safety**

- 4. Double insulated tools are equipped with a polarized plug (one blade is wider than the other.) This plug will fit in a polarized outlet only one way. If the plug does not fit fully in the outlet, reverse the plug. If it still does not fit, contact a qualified electrician to install a polarized outlet. Do not change the plug in any way. Double insulation eliminates the need for the three wire grounded power cord and grounded power supply system.
- Avoid body contact with grounded surfaces such as pipes, radiators, ranges and refrigerators. There is an increased risk of electric shock if your body is grounded.

- Do not expose power tools to rain or wet conditions. Water entering a power tool will increase the risk of electric shock.
- 7. Do not abuse the cord. Never use the cord to carry the tools or pull the plug from an outlet. Keep cord away from heat, oil, sharp edges or moving parts. Replace damaged cords immediately. Damaged cords increase the risk of electric shock.
- When operating a power tool outside, use an outdoor extension cord marked "W-A" or "W". These cords are rated for outdoor use and reduce the risk of electric shock.

# **Personal Safety**

- Stay alert, watch what you are doing and use common sense when operating a power tool. Do not use tool while tired or under the influence of drugs, alcohol, or medication. A moment of inattention while operating power tools may result in serious personal injury.
- 10. Dress properly. Do not wear loose clothing or jewelry. Contain long hair. Keep your hair, clothing, and gloves away from moving parts. Loose clothes, jewelry, or long hair can be caught in moving parts.
- 11. Avoid accidental starting. Be sure switch is off before plugging in. Carrying tools with your finger on the switch or plugging in tools that have the switch on invites accidents.
- 12. Remove adjusting keys or wrenches before turning the tool on. A wrench or a key that is left attached to a rotating part of the tool may result in personal injury.
- 13. Do not overreach. Keep proper footing and balance at all times. Proper footing and balance enables better control of the tool in unexpected situations.
- 14. Use safety equipment. Always wear eye protection. Dust mask, non-skid safety shoes, hard hat, or hearing protection must be used for appropriate conditions. Ordinary eye or sun glasses are NOT eye protection.

### **Tool Use and Care**

- 15. Use clamps or other practical way to secure and support the workpiece to a stable platform. Holding the work by hand or against your body is unstable and may lead to loss of control.
- 16. Do not force tool. Use the correct tool for your application. The correct tool will do the job better and safer at the rate for which it is designed.
- 17. Do not use tool if switch does not turn it on or off. Any tool that cannot be controlled with the switch is dangerous and must be repaired.
- 18. Disconnect the plug from the power source before making any adjustments, changing accessories, or storing the tool. Such preventive safety measures reduce the risk of starting the tool accidentally.
- 19. Store idle tools out of reach of children and other untrained persons. Tools are dangerous in the hands of untrained users.
- 20. Maintain tools with care. Keep cutting tools sharp and clean. Properly maintained tools with sharp cutting edges are less likely to bind and are easier to control.
- 21. Check for misalignment or binding of moving parts, breakage of parts, and any other condition that may affect the tools operation. If damaged, have the tool serviced before using. Many accidents are caused by poorly maintained tools.
- 22. Use only accessories that are recommended by the manufacturer for your model. Accessories that may be suitable for one tool, may become hazardous when used on another tool.

### SERVICE

23. Tool service must be performed only by qualified repair personnel. Service or maintenance performed by unqualified personnel could result in a risk of injury. 24. When servicing a tool, use only identical replacement parts. Follow instructions in the Maintenance section of this manual.

Use of unauthorized parts or failure to follow Maintenance instructions may create a risk of electric shock or injury.

**USE PROPER EXTENSION CORD:** Make sure your extension cord is in good condition. When using an extension cord, be sure to use one heavy enough to carry the current your product will draw. An undersized cord will cause a drop in line voltage resulting in loss of power and overheating. Table 1 shows the correct size to use depending on cord length and nameplate ampere rating. If in doubt, use the next heavier gage. The smaller the gage number, the heavier the cord.

Table 1: Minimum gage for cord

Amnoro Boting		Volts	Total length of cord in feet			
Amper	Ampere Rating		25 ft.	50 ft.	100 ft.	150 ft.
More Than	Not More Than			AWG		
0	6		18	16	16	14
6	10		18	16	14	12
10	12		16	16	14	12
12	16		14	12	Not Reco	mmended

# **SPECIFIC SAFETY RULES**

USB007-3

DO NOT let comfort or familiarity with product (gained from repeated use) replace strict adherence to sander safety rules. If you use this tool unsafely or incorrectly, you can suffer serious personal injury.

- Hold tool by insulated gripping surfaces when performing an operation where the cutting tool may contact hidden wiring or its own cord. Contact with a "live" wire will make exposed metal parts of the tool "live" and shock the operator.
- Always use safety glasses or goggles. Ordinary eye or sun glasses are NOT safety glasses.
- 3. Hold the tool firmly with both hands.
- Make sure the belt is not contacting the workpiece before the switch is turned on.

- 5. Keep hands away from rotating parts.
- 6. Do not leave the tool running. Operate the tool only when hand-held.
- This tool has not been waterproofed, so do not use water on the workpiece surface.
- 8. Ventilate your work area adequately when you perform sanding operations.
- Use of this tool to sand some products, paints and wood could expose user to dust containing hazardous substances. Use appropriate respiratory protection.

# SAVE THESE INSTRUCTIONS

# **⚠ WARNING:**

MISUSE or failure to follow the safety rules stated in this instruction manual may cause serious personal injury.

# FUNCTIONAL DESCRIPTION

# 003367

- 1. Lock button
- 2. Switch trigger

## **↑** CAUTION:

 Always be sure that the tool is switched off and unplugged before adjusting or checking function on the tool.

# Switch action

### **↑** CAUTION:

- Before plugging in the tool, always check to see that the switch trigger actuates properly and returns to the "OFF" position when released.
- Switch can be locked in "ON" position for ease of operator comfort during extended use. Apply caution when locking tool in "ON" position and maintain firm grasp on tool.

To start the tool, simply pull the switch trigger. Release the switch trigger to stop.


For continuous operation, pull the switch trigger and then push in the lock button.

To stop the tool from the locked position, pull the switch trigger fully, then release it.

# **ASSEMBLY**

## **⚠** CAUTION:

 Always be sure that the tool is switched off and unplugged before carrying out any work on the tool.




Lever

# Installing or removing abrasive belt

Pull the lever all the way out and install the belt over the rollers, then return the lever to the original position.

## **⚠** CAUTION:


 When installing the belt, make sure that the direction of the arrow on the back of the belt corresponds to the one on the tool itself.



1. Adjusting knob

# Adjusting belt tracking

While the belt is running, use the adjusting knob to center the belt tracking. Failure to do so can result in frayed belt edges and wear on the sander frame.



Dust spout
 Dust bag

# **Dust bag**

The use of the dust bag makes sanding operations clean and dust collection easy. To attach the dust bag, fit it onto the dust spout.

When the dust bag is about half full, remove the dust bag from the tool and pull the fastener out. Empty the dust bag of its contents, tapping it lightly so as to remove particles adhering to the insides which might hamper further collection.

# **OPERATION**

# 003393

# Sanding operation

### **↑** CAUTION:

 The tool should not be in contact with the workpiece surface when you turn the tool on or off. Otherwise a poor sanding finish or damage of the belt may result.


Hold the tool firmly with both hands. Turn the tool on and wait until it attains full speed. Then gently place the tool on the workpiece surface. Keep the belt flush with the workpiece at all times and move the tool back and forth.

Never force the tool. The weight of the tool applies adequate pressure. Excessive pressure may cause stalling, overheating of the motor, burning of the workpiece and possible kickback.


# **MAINTENANCE**

### **↑** CAUTION:

 Always be sure that the tool is switched off and unplugged before attempting to perform inspection or maintenance.



1. Limit mark



1. Brush holder cap

2. Screwdriver

# Replacing carbon brushes

Remove and check the carbon brushes regularly. Replace when they wear down to the limit mark. Keep the carbon brushes clean and free to slip in the holders. Both carbon brushes should be replaced at the same time. Use only identical carbon brushes.

Use a screwdriver to remove the brush holder caps. Take out the worn carbon brushes, insert the new ones and secure the brush holder caps.

To maintain product SAFETY and RELIABILITY, repairs, any other maintenance or adjustment should be performed by Makita Authorized or Factory Service Centers, always using Makita replacement parts.

# **ACCESSORIES**

# **⚠** CAUTION:

 These accessories or attachments are recommended for use with your Makita tool specified in this manual. The use of any other accessories or attachments might present a risk of injury to persons. Only use accessory or attachment for its stated purpose.

If you need any assistance for more details regarding these accessories, ask your local Makita service center.

- Abrasive belts
- Carbon plate

First-Class
Postage
Required

Post Office will
not deliver
without proper
postage.

Makita U.S.A., Inc. 14930 Northam Street La Mirada, CA 90638-5753

Hdallaallaalldalalddaladdalallalall

# **MAIL THIS PORTION**

# Your answers to the following questions are appreciated.

1. This product was purchased	from:		3. How did you learn abo	ut this product:	
Home Center	Other (	)	Magazine	Radio	
Hardware/Lumber Store			From Dealer	Exhibit	ion
Tool Distributor			Newspaper	From F	riend
Industrial Supply			Store Display	Previo	us Usage
Construction Supply			Catalog	Other	( )
2. Use of the product is intende	ed for:		4. Most favored points ar	e:	
Construction Trade			Design	Repair	Service
Industrial Maintenance			Features	Durabi	lity
Home Maintenance			Size	Power	
Hobby			Price	Other	( )
Other ( )			Makita Brand		
5. Any comments:					
, -5					
			. — . — . — . — . — .		
			WOREL NO		
DATE PURCHASED			MODEL NO.		
DATE PURCHASED  MONTH DAY	YE	AR			
	YE	AR	MODEL NO.		
	YE	AR			
MONTH DAY		AR		STATUS	
		AR		STATUS Married Sin	
MONTH DAY		AR			
MONTH DAY  INTL. LAST NAME / COMP.		AR			
MONTH DAY		AR			
MONTH DAY  INTL. LAST NAME / COMP.  STREET ADRESS		AR			
MONTH DAY  INTL. LAST NAME / COMP.		AR			
MONTH DAY  INTL. LAST NAME / COMP.  STREET ADRESS		AR			
MONTH DAY  INTL. LAST NAME / COMP.  STREET ADRESS		AR		Married Sin	
MONTH DAY  INTL. LAST NAME / COMP.  STREET ADRESS		AR		Married Sin	
MONTH DAY  INTL. LAST NAME / COMP.  STREET ADRESS  CITY	ANY NAME	AR	SERIAL NO.	Married Sin	
MONTH DAY  INTL. LAST NAME / COMP.  STREET ADRESS  CITY	ANY NAME	AR	SERIAL NO.	Married Sin	
MONTH DAY  INTL. LAST NAME / COMP.  STREET ADRESS  CITY	ANY NAME  ZIP CODE	S	SERIAL NO.	Married Sin	

Paste

Paste

Paste

Facsimile No: (714) 522-8133

Paste

Please return this portion by facsimile or mail.

Past

Paste

Paste

Dooto

Past

# **FACTORY SERVICE CENTERS**

# 1-800-4-MAKITA

# RETAIN THIS PORTION FOR YOUR RECORDS

### ARIZONA

3707 E. Broadway Rd., Ste. 6 Phoenix, AZ 85040 (602) 437-2850

### CALIFORNIA

41850 Christy St. Fremont, CA 94538-5107 (510) 657-9881

14930 Northam St. La Mirada, CA 90638-5753 (714) 522-8088

1970 Fulton Avenue Sacramento, CA 95825 (916) 482-5197

7674 Clairemont Mesa Blvd. San Diego, CA 92111 (858) 278-4471

16735 Saticoy St., Ste. 105 Van Nuys, CA 91406 (818) 782-2440

#### COLORADO

11839 E. 51st Ave. Denver, CO 80239-2709 (303) 371-2850

### FLORIDA

750 East Sample Road Pompano Beach, FL 33064 (954) 781-6333

#### GEORGIA

4680 River Green Parkway NW Duluth, GA 30096 (770) 476-8911

### ILLINOIS

1450 Feehanville Dr. Mt. Prospect, IL 60056-6011 (847) 297-3100

#### MARYLAND 7397 Washington Boulevard.

Suite 104 Elkridge, MD 21075 (410) 796-4401

### MASSACHUSETTS

232 Providence Hwy. Westwood, MA 02090 (781) 461-9754

### MINNESOTA

6427 Penn Ave. South Richfield, MN 55423 (612) 869-5199

### MISSOURI

9876 Watson Road St. Louis, MO 63126-2221 (314) 909-9889

### NEBRASKA

4129 S. 84th St. Omaha, NE 68127 (402) 597-2925

### NEVADA

3375 S. Decatur Blvd. Suites. 22 - 24 Las Vegas, NV 89102 (702) 368-4277

#### NEW JERSEY 251 Herrod Blvd.

251 Herrod Blvd. Dayton, NJ 08810-1539 (609) 655-1212

### **NEW YORK**

4917 Genessee Street Cheektowaga, NY 14225 (716) 685-9503

#### OREGON

828 19th Avenue, N.W. Portland, OR 97209 (503) 222-1823

### PENNSYLVANIA

1704 Babcock Blvd. Pittsburgh, PA 15209 (412) 822-7370

### **PUERTO RICO**

200 Guayama St. Hato Rey, PR 00917 (787) 250-8776

### TENNESSEE

1120 Elm Hill P. Suile 170 Nashville, TN 372 (615) 248-3321

### TEXAS

12801 Stemmons Fwy Ste. 809 Farmers Branch, TX 75234 (972) 243-1150

12701 Directors Dr. Stafford, TX 77477-3701 (281) 565-8665

3453 IH-35 North, Ste. 101 San Antonio, TX 78219 (210) 228-0676

# WISCONSIN

Lincoln Plaza Shopping Ctr. 2245 S. 108th St. West Allis, WI 53227 (414) 541-4776

### **CUSTOMER'S RECORD**

When you need service: Send	Date Purchased
complete tool (prepaid) to one of the Makita Factory Service	Dealer's Name & Address
Centers listed, or to an Authorized Makita Service Center. Be sure	
to attach a letter to the outside of the carton detailing the problem	Model No.
with your tool.	Serial No.

# WARNING

Some dust created by power sanding, sawing, grinding, drilling, and other construction activities contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. Some examples of these chemicals are:

- lead from lead-based paints,
- crystalline silica from bricks and cement and other masonry products, and
- arsenic and chromium from chemically-treated lumber.

Your risk from these exposures varies, depending on how often you do this type of work. To reduce your exposure to these chemicals: work in a well ventilated area, and work with approved safety equipment, such as those dust masks that are specially designed to filter out microscopic particles.

# MAKITA I IMITED ONE YEAR WARRANTY

# Warranty Policy

Every Makita tool is thoroughly inspected and tested before leaving the factory. It is warranted to be free of defects from workmanship and materials for the period of ONE YEAR from the date of original purchase. Should any trouble develop during this one year period, return the COMPLETE tool, freight prepaid, to one of Makita's Factory or Authorized Service Centers. If inspection shows the trouble is caused by defective workmanship or material, Makita will repair (or at our option, replace) without charge.

This Warranty does not apply where:

- repairs have been made or attempted by others:
- repairs are required because of normal wear and tear:
- the tool has been abused, misused or improperly maintained:
- alterations have been made to the tool.

IN NO EVENT SHALL MAKITA BE LIABLE FOR ANY INDIRECT, INCIDENTAL OR CONSEQUENTIAL DAMAGES FROM THE SALE OR USE OF THE PRODUCT. THIS DISCLAIMER APPLIES BOTH DURING AND AFTER THE TERM OF THIS WARRANTY.

MAKITA DISCLAIMS LIABILITY FOR ANY IMPLIED WARRANTIES, INCLUDING IMPLIED WARRANTIES OF "MERCHANTABILITY" AND "FITNESS FOR A SPECIFIC PURPOSE," AFTER THE ONE YEAR TERM OF THIS WARRANTY.

This Warranty gives you specific legal rights, and you may also have other rights which vary from state to state. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. Some states do not allow limitation on how long an implied warranty lasts, so the above limitation may not apply to you.

# Makita Corporation

3-11-8, Sumiyoshi-cho, Anjo, Aichi 446-8502 Japan